4900-6500MHz 34dBi Dual-Polarity & X-Polarized Dish Antenna

Model	STD6G34M2-PRO		
Electrical Specifications			
Frequency Range (MHz)	4900-5150	5150-6400	6400-6500
Polarization	Adjustable - Dual Polarized (Vertical and Horizontal) or X-Polarized (+45° and -45°)		
Gain	34 ±1 dBi		
VSWR	≤2.0	≤2.0	≤2.0
Horizontal Beamwidth	4°		
Vertical Beamwidth	3°		
F/B Ratio	≥42 dB		
Isolation	≥28 dB		
Nominal Impedance	50Ω		
Maximum Power	100W		
Lightning protection	DC Ground		

Mechanical Specifications	
Connector	2 x N-Female
Mounting Mast size	Φ40-70mm
Dimensions	Φ90cm
Weight	9.9 KG
Max. Wind Velocity	210km/h
Operating Temperature	-40～+60℃



H-Pol



V-Pol

SANNY TELECOM EQUIPMENT CO., LTD
Address: 3rd Floor, Building 3 Section B, Shihuzhou Industrial Zone, Sanshui District, Foshan City, Guangdong Province, China
Tel: +86 757 8766 0070 Fax: +86 757 8766 0500
Email: sales@sannytelecom.com Website: www.sannytelecom.com