


2300-2700MHz 27dBi Dual Polarized Dish Antenna


Model	STD24G27M2
Electrical Specifications	
Frequency Range	2300-2700MHz
Polarization	Adjustable - Dual Polarized (Vertical and Horizontal) or X-Polarized (+45° and -45°)
Gain	27 ±1 dBi
VSWR	≤2.0
Horizontal Beamwidth	6°
Vertical Beamwidth	5°
F/B Ratio	≥36dB
Isolation	≥26 dB
Nominal Impedance	50Ω
Maximum Power	50W
Lightning Protection	DC Ground



Mechanical Specifications	
Connector	2 x RP SMA-male with pigtail
Mounting Mast size	Φ50-Φ70mm
Dimensions	Φ90cm
Weight	9.8kg
Max. Wind Velocity	210km/h
Operating Temperature	-40~+60℃



H



E

SANNY TELECOM EQUIPMENT CO., LIMITED

Address: Room 201 Building 1, Wanyang Industrial Park, No.82 Xiaotang Industrial Avenue, Shishan Town, Nanhai District, Foshan City 528223, Guangdong Province, China

Tel: +86 757 8766 0070

Fax: +86 757 8766 0500

Email: sales@sannytelecom.com

Website: www.sannytelecom.com