



4900-5850MHz 30dBi Dual-Polarity & X-Polarized Dish Antenna

Model	STD5G30M2
Electrical Specifications	
Frequency Range	4900-5850MHz
Polarization	Adjustable - Dual Polarized (Vertical and Horizontal) or X-Polarized (+45° and -45°)
Gain	30 ± 0.5 dBi
VSWR	≤ 1.6
Horizontal Beamwidth	5°
Vertical Beamwidth	4°
F/B Ratio	≥32dB
Isolation	≥28dB
Nominal Impedance	50Ω
Maximum Power	100W
Lightning protection	DC Ground
Mechanical Specifications	
Connector	2 x N-Female
Mounting Mast size	Φ40-70mm
Dimensions	Φ60cm
Weight	4.6 KG
Max. Wind Velocity	210km/h
Operating Temperature	-40~+60℃



H-Pol



V-Pol

SANNY TELECOM EQUIPMENT CO., LTD

Address: Room 201 Building 1, Wanyang Industrial Park, No.82 Xiaotang Industrial Avenue, Shishan Town, Nanhai District, Foshan City 528223, Guangdong Province, China

Tel: +86 757 8766 0070

Fax: +86 757 8766 0500

Email: sales@sannytelecom.com

Website: www.sannytelecom.com